

DATE: March 2022

TECHNICAL DATA SHEET**PRODUCT DESCRIPTION:** SILICONE OIL SPRAY**CODE:** 80.0044

PROPERTIES AND AREA OF USE: Solution based on pure silicone oil that possesses anti-adhesive release and lubricating properties on a wide variety of materials, in particular synthetic, plastic and rubber surfaces. It also gives a good water repellency on the treated materials preventing the accumulation of electrostatic charges. It is effective as a polishing and protective on plastic parts and protects the gaskets from cracking, increasing their tightness and durability.

USE:

Use between +10° C and +25° C.

Use appropriate personal protection (gloves, glasses and masks). Clean the surface from impurities and dust. Remove any rust from the metals. Mask the parts not to be treated.

Shake the can vigorously for 2 minutes. Make a spray test on a separate surface. Spray with short and repeated jets to achieve the desired effect. Apply small amounts at a time until you get the desired effect. To unlock effectively and with less effort, let the product penetrate and wait a few minutes. Maximum efficiency is achieved after evaporation of the solvent.

Store in a dry place. Protect from direct sunlight and other heat sources. Use only during the dry season, in places protected from the wind, and in well-ventilated environments. Follow the warning texts on the labels.

TECH DATA: Tinplate spraycan 15 bars

Net content	400 ml
Appearance	Spray can with liquid under pressure
Color	no color
Odour	solvent
Density at 20°C	0,56 ÷ 0,60 g/ml
Pressure at 20°C	4,0 ± 0,5 bar
Pressure at 50°C	8,0 ± 0,5 bar
Flash point	< 0° C

LABELLING: all Areco Italia products comply with the current regulations on classification and labelling. Classification and distinction are made in accordance with the legislation of the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) pursuant to Regulation CLP 1272/2008 EC. Our safety data sheets comply with the current version REACH 1907/2006 EC, Article 31, Appendix II and subsequent amendments or updates.

ENVIRONMENT: Areco Italia undertakes to apply the formulations of the products without prohibited or restricted substances and to obtain the best possible performance. Caps and packaging are made of recyclable material.

DISPOSAL: Check that no paint residue remains in the container. Dispose of the empty container in the appropriate recycling containers. Containers containing paint residues must be disposed of at hazardous or special waste collection points.

DISCLAIMER: This technical information is based on scientific knowledge. They shall, however, be considered as a non-binding indication and shall not release the consumer from personally carrying out checks on the products with regard to their compatibility with the intended uses. The application and processing takes place outside the direct control of the manufacturer and are the sole responsibility of the user. Areco Italia is relieved of any liability if any damage is not attributable to specific causes attributable to Areco Italia itself.