

Safety Data Sheet
METALLIC GLITTER EFFECT spray



Safety Data Sheet dated 9/3/2022, version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: METALLIC GLITTER EFFECT spray

Trade code: 41.000

UFI: 5WW3-33JP-W000-56W8

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Spray painting decorative household, industrial and professional

1.3. Details of the supplier of the safety data sheet

Company:

ARECO ITALIA SPA Via Alfonso Capecelatro, 55 20148 Milano

Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. 0039 02 66101029

Competent person responsible for the safety data sheet:

commerciale@arecoitalia.it


1.4. Emergency telephone number

Centro Antiveleni - Ospedale di Niguarda - Milano - Tel. 0039 02 66101029


SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

 Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

 Warning, Skin Irrit. 2, Causes skin irritation.

 Warning, Eye Irrit. 2, Causes serious eye irritation.

 Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H315 Causes skin irritation.

Safety Data Sheet

METALLIC GLITTER EFFECT spray

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

None

Contains

acetone; propan-2-one; propanone

Special provisions according to Annex XVII of REACH and subsequent amendments:

Restricted to professional users.

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards










SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.






3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 25% - < 30%	acetone; propan-2-one; propanone	Index number: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 REACH No.: 01-21194713 30-49	 2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336 EUH066
>= 15% - < 20%	xylene	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-21194882 16-32	 2.6/3 Flam. Liq. 3 H226  3.1/4/Dermal Acute Tox. 4 H312  3.1/4/Inhal Acute Tox. 4 H332  3.2/2 Skin Irrit. 2 H315
>= 15% - < 20%	propane	Index number: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9 REACH No.: 01-21194869 44-21	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280

Safety Data Sheet

METALLIC GLITTER EFFECT spray

>= 7% - < 10%	butane	Index number: CAS: EC: REACH No.:	601-004-00-0 106-97-8 203-448-7 01-21194746 91-32	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280
>= 5% - < 7%	and isobutane	Index number: CAS: EC: REACH No.:	601-004-00-0 75-28-5 200-857-2 01-21194853 95-27	 2.2/1 Flam. Gas 1 H220  2.5/L Press Gas (Liq.) H280
>= 1% - < 2.5%	dimethyl carbonate	Index number: CAS: EC: REACH No.:	607-013-00-6 616-38-6 210-478-4 01-21195483 99-23	 2.6/2 Flam. Liq. 2 H225

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons:

Safety Data Sheet

METALLIC GLITTER EFFECT spray

- None in particular.
- 5.2. Special hazards arising from the substance or mixture
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
- 5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove all sources of ignition.
Remove persons to safety.
See protective measures under point 7 and 8.
- 6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
acetone; propan-2-one; propanone - CAS: 67-64-1

Safety Data Sheet

METALLIC GLITTER EFFECT spray

EU - TWA(8h): 1210 mg/m³, 500 ppm
 ACGIH - TWA(8h): 250 ppm - STEL: 500 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

xylene - CAS: 1330-20-7
 EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
 ACGIH - TWA(8h): 100 ppm - STEL: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair

propane - CAS: 74-98-6
 ACGIH - Notes: (D, EX) - Asphyxia
 VLE short - 1000 ppm

butane - CAS: 106-97-8
 ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair

and isobutane - CAS: 75-28-5
 ACGIH - STEL: 1000 ppm - Notes: (EX) - CNS impair
 VLE short - 1000 ppm

DNEL Exposure Limit Values
 N.A.

PNEC Exposure Limit Values
 N.A.

8.2. Exposure controls

Eye protection:
 Use close fitting safety goggles, don't use eye lens.

Protection for skin:
 No special precaution must be adopted for normal use.

Protection for hands:
 Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:
 Use adequate protective respiratory equipment.

Thermal Hazards:
 None

Environmental exposure controls:
 None

Appropriate engineering controls:
 None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Liquid aspect (under pressure), various colours.		
	--	--	
Odour:	Characteristic of solvent	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing	N.A.	--	--

Safety Data Sheet

METALLIC GLITTER EFFECT spray

point:			
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	Inf. 0 ° C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	Extremely flammable	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	a 20°C - 4,0 bar a 50°C - 8,0 bar	--	--
Vapour density:	N.A.	--	--
Relative density:	0,75 - 0,80 g/ml	--	--
Solubility in water:	NO	--	--
Solubility in oil:	SI	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

Safety Data Sheet

METALLIC GLITTER EFFECT spray

11.1. Information on toxicological effects

Toxicological information of the product:

DIAMANTATA-EFFETTO PERLINATO SPRAY

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

acetone; propan-2-one; propanone - CAS: 67-64-1

LD50 (RABBIT) ORAL: 5300 MG/KG

xylene - CAS: 1330-20-7

LD50 (RAT) ORAL: 5000 MG/KG

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

DIAMANTATA-EFFETTO PERLINATO SPRAY

Not classified for environmental hazards

Based on available data, the classification criteria are not met

12.2. Persistence and degradability

None

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

Safety Data Sheet

METALLIC GLITTER EFFECT spray

- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

- 14.1. UN number
ADR-UN number: 1950
IATA-Un number: 1950
IMDG-Un number: 1950
- 14.2. UN proper shipping name
ADR-Shipping Name: *ENTER PROPER SHIPPING NAME*
ADR-Shipping Name: AEROSOL
IATA-Shipping Name: *ENTER PROPER SHIPPING NAME*
IATA-Technical name: AEROSOL
IMDG-Shipping Name: *ENTER PROPER SHIPPING NAME*
IMDG-Technical name: AEROSOL
- 14.3. Transport hazard class(es)
ADR-Class: 2 5F
IATA-Class: 2.1
IATA-Label: 2.1
IMDG-Class: 2
IMDG-Class: 2
- 14.4. Packing group
ADR-Packing Group: -
IATA-Packing group: -
IMDG-Packing group: -
- 14.5. Environmental hazards
Marine pollutant: Marine pollutant
- 14.6. Special precautions for user
IATA-Passenger Aircraft: ----
IATA-Cargo Aircraft: 203
IMDG-Page: F-D, S-U
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
N.A.

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Safety Data Sheet

METALLIC GLITTER EFFECT spray

Regulation (EU) 2015/830
 Regulation (EU) n. 286/2011 (ATP 2 CLP)
 Regulation (EU) n. 618/2012 (ATP 3 CLP)
 Regulation (EU) n. 487/2013 (ATP 4 CLP)
 Regulation (EU) n. 944/2013 (ATP 5 CLP)
 Regulation (EU) n. 605/2014 (ATP 6 CLP)
 Regulation (EU) n. 2015/1221 (ATP 7 CLP)
 Regulation (EU) n. 2016/918 (ATP 8 CLP)
 Regulation (EU) n. 2016/1179 (ATP 9 CLP)
 Regulation (EU) n. 2017/776 (ATP 10 CLP)
 Regulation (EU) n. 2018/669 (ATP 11 CLP)
 Regulation (EU) n. 2018/1480 (ATP 13 CLP)
 Regulation (EU) n. 2019/521 (ATP 12 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3
 Restriction 40

Restrictions related to the substances contained:

Restriction 28
 Restriction 29
 Restriction 75

Volatile Organic compounds - VOCs = 615.00 g/l

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)
 Regulation (EC) nr 648/2004 (detergents).
 Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1
 Product belongs to category: P3a

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3:

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 H226 Flammable liquid and vapour.
 H312 Harmful in contact with skin.
 H332 Harmful if inhaled.
 H315 Causes skin irritation.
 H220 Extremely flammable gas.
 H280 Contains gas under pressure; may explode if heated.

Hazard class and	Code	Description
------------------	------	-------------

Safety Data Sheet

METALLIC GLITTER EFFECT spray

hazard category		
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press Gas (Liq.)	2.5/L	Gases under pressure (Liquefied gas)
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
 SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.

Safety Data Sheet

METALLIC GLITTER EFFECT spray

ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.